

ARETHA



Specifications:

| | |
|----------|-----------------------------|
| content: | 98.5% Polyester, 1.5% Nylon |
| backing: | 100% Polyester |
| finish: | iClean |
| repeat: | 13.5" x 13.5" |
| weight: | 15.06 oz. / lin. yd. |
| width: | 55 inches |

Flammability Passes:

California Tech. Bulletin #117-2013
 UFAC Class 1
 NFPA 260, Class 1

Performance:

| | |
|----------------------|---|
| abrasion: | Heavy Duty – Exceeds 100,000 cycles (Wyzenbeek – cotton duck Abradant) (ASTM D4157) |
| light fastness: | Class 4/40 hrs. min. (AATCC16A) |
| color fastness: | Class 3 (ASTM D3597, AATCC 8) Wet Class 4 (ASTM D3597, AATCC 8) Dry |
| physical properties: | Class 3 (ASTM D3511) Brush Pill 201 lbs. warp, 123 lbs. weft (ASTM D5034) Breaking Strength 92 lbs. warp, 43 lbs. weft (ASTM D4034) Seam Slippage |
| recommended use: | Upholstery |
| made in: | China |

Care & Cleanability:

Cleaning code **W** - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam-to-seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).