
Culp, Inc.



Flammability Passes:

California Tech. Bulletin #117-2013 UFAC Class 1 NFPA 260 Class 1

Specifications:

content:	98% Polyester; 2% Nylon
backing:	Polyester scrim
finish: Repeat:	i-clean, a high performance stain repellant based on .Nano technology. H: 13.5″ V: 13.5″
weight:	15.04 oz./lin. yd.
width:	54 inches

Heavy Duty – 100,000 cycles
(Wyzenbeek – Cotton duck Abradant) (ASTM D4157)
Class 4/40 hrs. min. (AATCC16A)
Class 3 (ASTM D3597, AATCC 8) Wet
Class 4 (ASTM D3597, AATCC 8) Dry
Class 3 (ASTM D3511) Brush Pill
201 lbs. warp, 123 lbs. weft (ASTM D5034) Breaking Strength
92 lbs. warp, 43 lbs. weft (ASTM D4034) Seam Slippage

made in:

China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).