





## Specifications:

content: 100% Polyurethane

backing: 43% Leather, 40% Polyester; 17%

Cotton

finish: n/a Repeat: n/a

weight: 24.96 oz. / lin. yd.

width: 54 inches

## Flammability Passes:

California Tech. Bulletin #117-2013

UFAC Class 1 NFPA 260 Class 1 **MVSS 302** 

## Performance:

abrasion: Heavy Duty – Exceeds 100,000 cycles

(Wyzenbeek - Cotton duck abradant) (ASTM D4157)

light fastness: Class 4/200 hrs. min. (AATCC16A) color fastness: Class 4 (ASTM D3597, AATCC 8) Wet

Class 4 (ASTM D3597, AATCC 8) Dry

physical properties: 104 lbs. warp, 116 lbs. weft (ASTM D5034) Breaking Strength

43 lbs. warp, 56 lbs. weft (ASTM D4034) Seam Slippage

Recommended use: Upholstery

made in: China

## Care & Cleanability:

Cleaning code  $\mathbf{W}$  – Spot clean with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org.)>