

Largo



Specifications:

content: 100% Polyester

backing: **None**

finish: Anti flammability

repeat: None"

weight: 8.8 oz / lin. yd.

width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013

UFAC Class 1

NFPA 260 Class 1

NFPA 701 small scale - pass

Performance:

abrasion: Heavy Duty –Cycles 30,000
(Wyzenbeek – Cotton duck Abradant) (ASTM D4157)

light fastness: Class 4/60 hrs. min. (AATCC16A)

color fastness: Class 3 (ASTM D3597, AATCC 8) Wet
Class 3 (ASTM D3597, AATCC 8) Dry

physical properties: Class 4 (ASTM D3511) Brush Pill
82 warp, lbs.72 weft (ASTM D5034) Breaking Strength
67 warp, 57 lbs. weft (ASTM D4034) Seam Slippage

made in: Columbia, SA

Care & Cleanability:

Cleaning code **W** - Spot clean only with water based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam to seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).